

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : PhD Dry Shampoo
Product code : AF-458
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture : Cosmetics

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Living Proof, Inc.
One Design Center Place
Suite 600
Boston, MA 02210
T: 617-621-1800 F: 617-621-1880
E: questions@livingproof.com
livingproof.com

Living Proof
Fifth Floor, Union House
182-194 Union Street
London SE1 0LH

Living Proof
Wiesenstr. 21, D-40549
Düsseldorf, Germany

1.4. Emergency telephone number

Emergency number : Chemtrec - +1-800-424-9300 or +1-703-527-3887

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aerosol, Category 1 H222;H229
Serious eye damage/eye irritation, Category 2 H319
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Danger

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H319 - Causes serious eye irritation.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
EUH-statements	: EUH208 - Contains D-Limonene(5989-27-5). May produce an allergic reaction.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5	< 8	Flam. Liq. 2, H225 Eye Irrit. 2, H319
D-Limonene	CAS-No.: 5989-27-5 EC-No.: 227-813-5 EC Index-No.: 601-096-00-2	< 0.03	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 3, H412

INGREDIENTS : Isobutane, Propane, Alcohol Denat, Oryza Sativa (Rice) Starch, Hydroxypropylcellulose, Microcrystalline Cellulose, Dipropylene Glycol, Cetrimonium Chloride, Caprylyl Glycol, Distearidimonium Hectorite, Pentylene Glycol, Propanediol, Citronellyl Methylcrotonate, Cellulose, Water/Eau/Aqua, Furcellaria Lumbricalis Extract, Zeolite, Ethylcellulose, C12-15 Alketh-2, Fragrance/Parfum, Ethylhexylglycerin, Limonene, Citronellol, Hexyl Cinnamal, Benzyl Salicylate, Citral, Linalool.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. If symptoms persist call a doctor.
First-aid measures after skin contact	: If skin irritation occurs: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical attention if irritation develops.

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Not expected to be a primary route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact	: Eye irritant upon direct contact. Causes serious eye irritation.
------------------------------------	--------------------------------------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam. Water spray.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol. Cool closed containers exposed to fire with water spray. Contains gas under pressure; may explode if heated. Thermal decomposition may produce : Carbon oxides (CO, CO2).
Explosion hazard	: Heat may build pressure in tank and containers, rupturing closed vessels, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Thermal decomposition can lead to the release of irritating gases and vapours.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.
Protective equipment for firefighters	: Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Avoid contact with eyes.
------------------	-------------------------------------------------------------------------

6.1.1. For non-emergency personnel

Protective equipment	: No special protection required.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with eyes. Do not breathe vapours. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Aerosol Storage level 1. Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Incompatible materials : Strong oxidizing agents.

7.3. Specific end use(s)

For further information see section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

isobutane (75-28-5)	
Austria - Occupational Exposure Limits	
Local name	Butan (beide Isomeren): Isobutan (2-Methylpropan) (R 600a)
MAK (OEL TWA)	1900 mg/m³
MAK (OEL TWA) [ppm]	800 ppm
MAK (OEL STEL)	3800 mg/m³ (3x 60(Mow) min)
MAK (OEL STEL) [ppm]	1600 ppm (3x 60(Mow) min)
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan
OEL TWA [ppm]	1000
OEL STEL	2370 mg/m³
OEL STEL [ppm]	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Estonia - Occupational Exposure Limits	
Local name	Isobutaan (2-metüülpropaan)
OEL TWA	1900 mg/m³
OEL TWA [ppm]	800 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	i-Butaani (2-Metyylipropaani)
HTP (OEL TWA) [1]	1900 mg/m³
HTP (OEL TWA) [2]	800 ppm
HTP (OEL STEL)	2400 mg/m³
HTP (OEL STEL) [ppm]	1000 ppm

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isobutane (75-28-5)	
Remark	Happea syrjäyttämällä tukahduttavat kaasut.
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
VME (OEL TWA)	1900 mg/m³
VME (OEL TWA) [ppm]	800 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	2400 mg/m³
AGW (OEL TWA) [2]	1000 ppm
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Isobutane
Regulatory reference	Chemical Agents Code of Practice 2021
Portugal - Occupational Exposure Limits	
Local name	Butano, todos os isómeros
OEL STEL [ppm]	1000 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Slovakia - Occupational Exposure Limits	
Local name	Bután s obsahom ≥ 0,1% butadiénu (izo-bután)
NPHV (OEL TWA) [1]	2400 mg/m³ (TSH)
NPHV (OEL TWA) [2]	1000 ppm (TSH)
Remark	Kategória karcinogénov 1A – Dokázaný karcinogén pre ľudí
Regulatory reference	Nariadenie vlády č. 356/2006 Z. z. (235/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	izobutan
OEL TWA	2400 mg/m³
OEL TWA [ppm]	1000 ppm
OEL STEL	9600 mg/m³
OEL STEL [ppm]	4000 ppm
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
USA - ACGIH - Occupational Exposure Limits	
Local name	Isobutane
ACGIH OEL TWA [ppm]	1000 ppm
ACGIH OEL STEL [ppm]	1000 ppm (EX - Explosion hazard)
Regulatory reference	ACGIH 2022
propane (74-98-6)	
Austria - Occupational Exposure Limits	
Local name	Propan (R 290)
MAK (OEL TWA)	1800 mg/m³
MAK (OEL TWA) [ppm]	1000 ppm
MAK (OEL STEL)	3600 mg/m³

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)	
MAK (OEL STEL) [ppm]	2000 ppm
Regulatory reference	BGBI. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Пропан
OEL TWA	1800 mg/m³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Denmark - Occupational Exposure Limits	
Local name	Propan (Flaskegas)
OEL TWA [1]	1800 mg/m³
OEL TWA [2]	1000 ppm
OEL STEL	3600 mg/m³
OEL STEL [ppm]	2000 ppm
Regulatory reference	BEK nr 1054 af 28/06/2022
Estonia - Occupational Exposure Limits	
Local name	Propaan
OEL TWA	1800 mg/m³
OEL TWA [ppm]	1000 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	Propaani
HTP (OEL TWA) [1]	1500 mg/m³
HTP (OEL TWA) [2]	800 ppm
HTP (OEL STEL)	2000 mg/m³
HTP (OEL STEL) [ppm]	1100 ppm
Remark	Happea syrjäyttämällä tukahduttavat kaasut.
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Propan
AGW (OEL TWA) [1]	1800 mg/m³
AGW (OEL TWA) [2]	1000 ppm
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)	
Regulatory reference	TRGS900
Greece - Occupational Exposure Limits	
Local name	Προπάνιο
OEL TWA	1800 mg/m ³
OEL TWA [ppm]	1000 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Ireland - Occupational Exposure Limits	
Local name	Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane
OEL STEL [ppm]	3000 ppm (calculated (Aliphatic hydrocarbon gases - Alkanes (C1-C4)))
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
OEL chemical category	Simple asphyxiant
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
Local name	Propāns
OEL TWA	1800 mg/m ³
OEL TWA [ppm]	1000 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2015. gada 7. aprīlī noteikumiem Nr. 163)
Poland - Occupational Exposure Limits	
Local name	Propan
NDS (OEL TWA)	1800 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	1000 ppm
Romania - Occupational Exposure Limits	
Local name	Propan
OEL TWA	1400 mg/m ³
OEL TWA [ppm]	778 ppm
OEL STEL	1800 mg/m ³
OEL STEL [ppm]	1000 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovenia - Occupational Exposure Limits	
Local name	propan
OEL TWA	1800 mg/m ³
OEL TWA [ppm]	1000 ppm
OEL STEL	7200 mg/m ³
OEL STEL [ppm]	4000 ppm

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propane (74-98-6)	
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Propano
VLA-ED (OEL TWA) [2]	1000 ppm Hidrocarburos alifáticos alcanos (C1 – C4) y sus mezclas, gases (Butano; Etano; Metano; Propano)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Norway - Occupational Exposure Limits	
Local name	Propan
Grenseverdi (OEL TWA) [1]	900 mg/m ³
Grenseverdi (OEL TWA) [2]	500 ppm
Korttidsverdi (OEL STEL)	1125 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	625 ppm (value calculated)
Regulatory reference	FOR-2021-06-28-2248
USA - ACGIH - Occupational Exposure Limits	
Local name	Propane
ACGIH OEL TWA [ppm]	1000 ppm
Remark (ACGIH)	TLV® Basis: Simple Asphyxiant
ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Regulatory reference	ACGIH 2022
Ethyl alcohol (64-17-5)	
Austria - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)
MAK (OEL TWA)	1900 mg/m ³
MAK (OEL TWA) [ppm]	1000 ppm
MAK (OEL STEL)	3800 mg/m ³ (3x 60(Mow) min)
MAK (OEL STEL) [ppm]	2000 ppm (3x 60(Mow) min)
OEL C	3800 mg/m ³
OEL C [ppm]	2000 ppm
Regulatory reference	BGBl. II Nr. 156/2021
Belgium - Occupational Exposure Limits	
Local name	Alcool éthylique # Ethanol
OEL TWA	1907 mg/m ³
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Етилов алкохол
OEL TWA	1000 mg/m ³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
Croatia - Occupational Exposure Limits	
Local name	Etanol; etil-alkohol
GVI (OEL TWA) [1]	1900 mg/m³
GVI (OEL TWA) [2]	1000 ppm
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)
PEL (OEL TWA)	1000 mg/m³
PEL (OEL TWA) [ppm]	522 ppm
NPK-P (OEL C)	3000 mg/m³
NPK-P (OEL C) [ppm]	1566 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)
OEL TWA [1]	1900 mg/m³
OEL TWA [2]	1000 ppm
Regulatory reference	BEK nr 1054 af 28/06/2022
Estonia - Occupational Exposure Limits	
Local name	Etanool (etüülalkohol)
OEL TWA	1000 mg/m³
OEL TWA [ppm]	500 ppm
OEL STEL	1900 mg/m³
OEL STEL [ppm]	1000 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
Local name	Etanoli
HTP (OEL TWA) [1]	1900 mg/m³
HTP (OEL TWA) [2]	1000 ppm
HTP (OEL STEL)	2500 mg/m³
HTP (OEL STEL) [ppm]	1300 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Alcool éthylique
VME (OEL TWA)	1900 mg/m³
VME (OEL TWA) [ppm]	1000 ppm
VLE (OEL C/STEL)	9500 mg/m³
VLE (OEL C/STEL) [ppm]	5000 ppm
Remark	Valeurs recommandées/admises

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Ethanol
AGW (OEL TWA) [1]	380 mg/m³
AGW (OEL TWA) [2]	200 ppm
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Greece - Occupational Exposure Limits	
Local name	Αιθνόλη
OEL TWA	1900 mg/m³
OEL TWA [ppm]	1000 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	ETIL-ALKOHOL
AK (OEL TWA)	1900 mg/m³
CK (OEL STEL)	3800 mg/m³
Remark	N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Ethanol [Ethyl alcohol]
OEL TWA [1]	1900 mg/m³
OEL TWA [2]	1000 ppm
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
Local name	Etilspirts (etanols)
OEL TWA	1000 mg/m³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Etanolis (etilo alkoholis)
IPRV (OEL TWA)	1000 mg/m³
IPRV (OEL TWA) [ppm]	500 ppm
TPRV (OEL STEL)	1900 mg/m³
TPRV (OEL STEL) [ppm]	1000 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
Netherlands - Occupational Exposure Limits	
Local name	Ethanol
TGG-8u (OEL TWA)	260 mg/m ³
TGG-15min (OEL STEL)	1900 mg/m ³
Remark	Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
MAC chemical category	Skin notation
Regulatory reference	Arbeidsomstandighedenregeling 2022
Poland - Occupational Exposure Limits	
Local name	Etanol (alkohol etylowy)
NDS (OEL TWA)	1900 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Etanol (Álcool etílico)
OEL TWA [ppm]	1000 ppm
OEL STEL [ppm]	1000 ppm
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Remark	A3 (Agente carcinogénico confirmado nos animais de laboratório com relevância desconhecida no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Alcool etilic/Etanol
OEL TWA	1900 mg/m ³
OEL TWA [ppm]	1000 ppm
OEL STEL	9500 mg/m ³
OEL STEL [ppm]	5000 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovakia - Occupational Exposure Limits	
Local name	Etylalkohol (etanol)
NPHV (OEL TWA) [1]	960 mg/m ³
NPHV (OEL TWA) [2]	500 ppm
NPHV (OEL STEL)	1920 mg/m ³
NPHV (OEL STEL) [ppm]	1000 ppm
NPHV (OEL C)	1920 mg/m ³
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	etanol (etilalkohol)
OEL TWA	960 mg/m ³

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
OEL TWA [ppm]	500 ppm
OEL STEL	1920 mg/m ³
OEL STEL [ppm]	1000 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Etanol (Alcohol etílico)
VLA-ED (OEL TWA) [1]	1910 mg/m ³
VLA-ED (OEL TWA) [2]	1000 ppm
VLA-EC (OEL STEL)	1910 mg/m ³
VLA-EC (OEL STEL) [ppm]	1000 ppm
Remark	s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas Base de datos de productos fitosanitarios http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Etanol
NGV (OEL TWA)	1000 mg/m ³
NGV (OEL TWA) [ppm]	500 ppm
KTV (OEL STEL)	1900 mg/m ³
KTV (OEL STEL) [ppm]	1000 ppm
Remark	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
Norway - Occupational Exposure Limits	
Local name	Etanol
Grenseverdi (OEL TWA) [1]	950 mg/m ³
Grenseverdi (OEL TWA) [2]	500 ppm
Korttidsverdi (OEL STEL)	1187.5 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	625 ppm (value calculated)
Regulatory reference	FOR-2021-06-28-2248
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanol
ACGIH OEL STEL [ppm]	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2022

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Cornstarch (9005-25-8)	
Belgium - Occupational Exposure Limits	
Local name	Amidon # Zetmeel
OEL TWA	10 mg/m³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Czech Republic - Occupational Exposure Limits	
Local name	Prach škrobu
PEL (OEL TWA)	4 mg/m³
Remark	Prachy s převážně dráždivým účinkem.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Greece - Occupational Exposure Limits	
Local name	Άμυλο
OEL TWA	10 mg/m³ εισπν. 5 mg/m³ αναπν.
OEL STEL	5 mg/m³ total respirable (edit STEL to TWA)
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Ireland - Occupational Exposure Limits	
Local name	Starch
OEL TWA [1]	10 mg/m³ total inhalable dust 4 mg/m³ respirable dust
OEL STEL	4 mg/m³ total respirable (edit 15 min to 8 hours)
Regulatory reference	Chemical Agents Code of Practice 2021
Portugal - Occupational Exposure Limits	
Local name	Amido
OEL TWA	10 mg/m³
Remark	A4 (Agente não classificável como carcinogénico no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Spain - Occupational Exposure Limits	
Local name	Almidón
VLA-ED (OEL TWA) [1]	10 mg/m³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
USA - ACGIH - Occupational Exposure Limits	
Local name	Starch
ACGIH OEL TWA	10 mg/m³
Remark (ACGIH)	TLV® Basis: Dermatitis. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2022
Cellulose (9004-34-6)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m³ PAPIER (LEICHTSTAUB VON), EINATEMBARE FRAKTION
OEL C	10 mg/m³ PAPIER (LEICHTSTAUB VON), EINATEMBARE FRAKTION

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Cellulose (9004-34-6)	
Belgium - Occupational Exposure Limits	
Local name	Cellulose # Cellulose
OEL TWA	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Croatia - Occupational Exposure Limits	
Local name	Celuloza
GVI (OEL TWA) [1]	10 mg/m ³ (total dust, inhalable particles) 4 mg/m ³ (respirable dust)
KGVI (OEL STEL)	20 mg/m ³ (total dust, inhalable particles)
Regulatory reference	Pravilnik o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	6 mg/m ³ Jiné prachy s dráždivým účinkem: prach papíru
Denmark - Occupational Exposure Limits	
OEL TWA [1]	3 mg/m ³ ORGANISK STØV, TOTAL
Estonia - Occupational Exposure Limits	
Local name	Tselluloos
OEL TWA	10 mg/m ³ peentolm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 15.05.2021, 1)
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	5 mg/m ³ Selluloosapöly
HTP (OEL C)	10 mg/m ³ Selluloosapöly
France - Occupational Exposure Limits	
Local name	Cellulose (fibre de papier)
VME (OEL TWA)	10 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Ireland - Occupational Exposure Limits	
Local name	Cellulose
OEL TWA [1]	10 mg/m ³
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	Cellulosa
OEL TWA	10 mg/m ³
Latvia - Occupational Exposure Limits	
Local name	Celuloze
OEL TWA	2 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Popieriaus Dulkės

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Cellulose (9004-34-6)	
IPRV (OEL TWA)	2 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	Celulose
OEL TWA	10 mg/m ³
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Celuloză
OEL TWA	10 mg/m ³ (dust, inhalable fraction)
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Spain - Occupational Exposure Limits	
Local name	Celulosa
VLA-ED (OEL TWA) [1]	10 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
USA - ACGIH - Occupational Exposure Limits	
Local name	Cellulose
ACGIH OEL TWA	10 mg/m ³
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2022
Oxydipropanol (25265-71-8)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	100 mg/m ³ (E)
AGW (OEL C)	200 mg/m ³
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 11 - Summe aus Dampf und Aerosolen
Regulatory reference	TRGS900
Slovenia - Occupational Exposure Limits	
Local name	oksidipropanol (dipropilenglikol)
OEL TWA	100 mg/m ³
OEL STEL	200 mg/m ³
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
D-Limonene (5989-27-5)	
Finland - Occupational Exposure Limits	
Local name	D-Limoneeni
HTP (OEL TWA) [1]	140 mg/m ³
HTP (OEL TWA) [2]	25 ppm

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

D-Limonene (5989-27-5)	
HTP (OEL STEL)	280 mg/m ³
HTP (OEL STEL) [ppm]	50 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	(R)-p-Mentha-1,8-dien (D-Limonen)
AGW (OEL TWA) [1]	28 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); H - hautresorptiv; Sh - Hautsensibilisierender Stoff; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Chemical category	Skin notation, Skin sensitization
Regulatory reference	TRGS900
Slovenia - Occupational Exposure Limits	
Local name	(R)-p-menta-1,8-dien (D-limonen)
OEL TWA	28 mg/m ³
OEL TWA [ppm]	5 ppm
OEL STEL	112 mg/m ³
OEL STEL [ppm]	20 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	d-Limoneno
VLA-ED (OEL TWA) [1]	168 mg/m ³
VLA-ED (OEL TWA) [2]	30 ppm
Remark	Sen (Sensibilizante), vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante).
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Norway - Occupational Exposure Limits	
Local name	d-limonen (Limonen)
Grønseverdi (OEL TWA) [1]	140 mg/m ³
Grønseverdi (OEL TWA) [2]	25 ppm
Korttidsverdi (OEL STEL)	175 mg/m ³ (value calculated)

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

D-Limonene (5989-27-5)	
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)
Remark	A: Kjemikalier som skal betraktes som at de fremkaller allergi eller annen overfølsomhet i øynene eller luftveier, eller som skal betraktes som at de fremkaller allergi ved hudkontakt.
OEL chemical category	Allergenic substance
Regulatory reference	FOR-2021-06-28-2248
Citral (5392-40-5)	
Belgium - Occupational Exposure Limits	
Local name	Citral (vapeur et aérosol) # Citral (damp en aérosol)
OEL TWA	32 mg/m ³
OEL TWA [ppm]	5 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
OEL chemical category	Skin
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Ireland - Occupational Exposure Limits	
Local name	Citral
OEL TWA [2]	5 ppm IFV (Inhalable Fraction and Vapour)
OEL STEL [ppm]	15 ppm (calculated)
Regulatory reference	Chemical Agents Code of Practice 2021
Poland - Occupational Exposure Limits	
Local name	3,7-Dimetylookta-2,6-dienal (cytral)
NDS (OEL TWA)	27 mg/m ³
NDSch (OEL STEL)	54 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA [ppm]	5 ppm
OEL chemical category	Sensitizer, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure
Spain - Occupational Exposure Limits	
Local name	Citral
VLA-ED (OEL TWA) [2]	5 ppm

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Citral (5392-40-5)	
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), Sen (Sensibilizante), FIV (Fracción inhalable y vapor. La notación FIV señala a aquellos agentes químicos que se pueden presentar en el ambiente de trabajo, tanto en forma de materia particulada como vapor, por lo que las dos fases pueden coexistir, contribuyendo ambas a la exposición. Esta situación se puede dar, principalmente, en los siguientes casos: • Cuando el agente en cuestión tiene un valor "intermedio" de presión de vapor (en estos casos se tiene en cuenta la relación entre su concentración en el aire saturado de vapor y el valor del VLA-ED® y la nota se asigna, generalmente, cuando el cociente entre ambas cantidades se encuentra entre 0.1 y 10). • Por razón de la forma de uso del agente químico (por ejemplo, pulverización). • En los procesos que conlleven cambios importantes de temperatura que puedan afectar al estado físico del agente químico. • En los procesos en los que una fracción significativa del vapor puede disolverse o adsorberse en las partículas de otra sustancia, a semejanza de lo que ocurre con los agentes solubles en agua en ambientes con humedad elevada).
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
USA - ACGIH - Occupational Exposure Limits	
Local name	Citral
ACGIH OEL TWA [ppm]	5 ppm (IFV - Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Body weight eff; URT irr; eye dam. Notations: Skin; DSEN; A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer
Regulatory reference	ACGIH 2022
Zeolite (1318-02-1)	
Latvia - Occupational Exposure Limits	
OEL TWA	2 mg/m³ (artificial and natural (Silicates and aluminosilicates))
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	10 mg/m³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

None in normal use conditions. Normal use of this product shall imply use in accordance with the instructions on the packaging.

8.2.2. Personal protection equipment

Personal protective equipment:

None in normal use conditions. Normal use of this product shall imply use in accordance with the instructions on the packaging.

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

None in normal use conditions

8.2.2.2. Skin protection

Hand protection:

None in normal use conditions

8.2.2.3. Respiratory protection

Respiratory protection:

None in normal use conditions

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: White.
Appearance	: Cloudy. Dispersion.
Odour	: Characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Extremely flammable aerosol.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : < 94%

9.2.2. Other safety characteristics

Gas group : Compressed gas
VOC content : < 94 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating will cause a rise in pressure with a risk of bursting. Avoid ignition sources. Avoid temperature above. 50 °C.

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

10.3. Possibility of hazardous reactions

Heating may cause a fire or explosion.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Ethyl alcohol (64-17-5)

LD50 oral rat	7060 mg/kg
LD50 oral	10470 mg/kg bodyweight
LD50 dermal	15800 mg/kg bodyweight
LC50 Inhalation - Rat	133.8 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	> 99999 mg/l

D-Limonene (5989-27-5)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rabbit	> 5000 mg/kg Source: National Library of Medicine
Skin corrosion/irritation	: Not classified (On basis of test data)
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (On basis of test data)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)

D-Limonene (5989-27-5)

IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

Ethyl alcohol (64-17-5)

LOAEL (oral, rat, 90 days)	3200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	1730 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)

NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
--------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

PhD Dry Shampoo

Vaporizer	Aerosol
-----------	---------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : None known

11.2.2. Other information

Other information : Historical Data, not tested on Animals for cosmetics, Likely routes of exposure: inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Historical Data, not tested on Animals for cosmetics.
Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Ethyl alcohol (64-17-5)

LC50 - Fish [1]	12 – 16 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
LC50 - Other aquatic organisms [1]	5012 mg/l 48 hours- daphnia
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Other aquatic organisms [1]	5012 mg/l waterflea
EC50 - Other aquatic organisms [2]	275 mg/l
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	275 mg/l Source: ECHA
ErC50 other aquatic plants	4432 mg/l
NOEC (acute)	9.6 mg/l Daphnia magna
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
NOEC chronic crustacea	9.6 mg/l

D-Limonene (5989-27-5)

LC50 - Fish [1]	720 µg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	702 µg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	0.307 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0.32 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

D-Limonene (5989-27-5)

EC50 72h - Algae [2]

0.214 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Ethyl alcohol (64-17-5)

Partition coefficient n-octanol/water (Log Pow)

-0.35 (at 24 °C (at pH 7.4)

D-Limonene (5989-27-5)

Partition coefficient n-octanol/water (Log Pow)

4.38 Source: ECHA Registered substances

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations







: Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials

: Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1 (LTD QTY)	2.1 (LTD QTY)	2.1	2.1
		 		

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
Transport regulations (IATA) : May also be transported as a consumer commodity when classified as ID8000 under Class 9 Miscellaneous Dangerous Goods, Proper Shipping Name and UN number must be shown on packaging.				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : < 94 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
WGK remark	: Most stringent classification due to insufficient data.
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen	: Ethyl alcohol is listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: Ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: Ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: Ethyl alcohol is listed

Denmark

Danish National Regulations	: Young people under 18 years are not allowed to use the product
-----------------------------	------------------------------------------------------------------

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Other information	: None.
-------------------	---------

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains D-Limonene(5989-27-5). May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

PhD Dry Shampoo

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	Expert judgment
Eye Irrit. 2	H319	Calculation method

Safety Data Sheet (SDS), EU

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.