

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Trade name : LIVING PROOF FULL DRY VOLUME BLAST

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cosmetics

1.3. Details of the supplier of the safety data sheet

Living Proof, Inc.
1 Design Center Place, Suite 600
Boston, MA, 02210-2349
T: 617-621-1800 F: 617-621-1880
questions@livingproof.com
livingproof.com

1.4. Emergency telephone number

Emergency number : Chemtrec - +1-800-424-9300 or +1 703-527-3887

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable aerosol Category 1 H222

Full text of H statements : see section 16

2.2. Label elements**GHS-US labeling**

Hazard pictograms (GHS-US) :



GHS02

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H222 - Extremely flammable aerosol
Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients**3.1. Substance**

Not applicable

3.2. Mixture

INGREDIENTS: Hydrofluorocarbon 152a, Alcohol Denat., VP/VA Copolymer, VA/Crotonates/Vinyl Neodecanoate Copolymer, Acrylonitrile/Methyl Methacrylate Crosspolymer, Water/Eau/Aqua, Aluminum Starch Octenylsuccinate, Zeolite, Butane, Fragrance/Parfum, Ethylcellulose, Propylene Glycol Dibenzoate, Aminomethyl Propanol, Benzophenone-3, Acrylates Copolymer, Magnesium Carbonate, Glycyrrhizic Acid, Magnesium Hydroxide, Linalool, Butylphenyl Methylpropional, Citronellol, Citral, Limonene.

LIVING PROOF FULL DRY VOLUME BLAST

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Ethyl alcohol	(CAS No) 64-17-5	<20	Flam. Liq. 2, H225 Carc. 1A, H350 NOTE: Alcoholic beverages only; not applicable to this product. This product uses denatured alcohol.

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person; If affected person feels unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If affected person is experiencing breathing difficulty, allow affected person to breathe fresh air. Allow affected person to rest.
- First-aid measures after skin contact : If adverse skin reaction occurs, remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Cool closed containers exposed to fire with water spray. In closed containers, pressure build up could result in distortion, blowing and in extreme cases bursting of the container.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : Heating will cause rise in pressure with risk of bursting. Avoid ignition sources. Avoid temperature above 50°C.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Clear up spills immediately and dispose of waste safely. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep product away from all heat sources. No open flames. No smoking. Avoid contact with eyes. Do not breathe vapors.

LIVING PROOF FULL DRY VOLUME BLAST

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials : Sources of ignition.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethyl alcohol (64-17-5)		
ACGIH	ACGIH STEL (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	3300 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm

8.2. Exposure controls

Personal protective equipment : None needed.
Hand protection : None needed.
Eye protection : None needed.
Skin and body protection : None needed.
Respiratory protection : None needed.
Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Off-white
Odor : Characteristic
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Vapor pressure : 3,620 – 4,654 mm Hg
Relative density : No data available
Relative vapor density at 20 °C : No data available
Solubility : No data available
Log Pow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

LIVING PROOF FULL DRY VOLUME BLAST

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

VOC% : 20%
Gas group : Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating will cause rise in pressure with risk of bursting. Avoid ignition sources. Avoid temperature above 50°C.

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

10.3. Possibility of hazardous reactions

Heating may cause a fire or explosion.

10.4. Conditions to avoid

Extremely high or low temperatures. Direct sunlight. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethyl alcohol (64-17-5)	
LD50 oral rat	7060 mg/kg (Historical information; not tested on animals for cosmetics)
LC50 inhalation rat (mg/l)	124.7 mg/l/4h (Historical information; not tested on animals for cosmetics)
ATE US (oral)	7060.000 mg/kg body weight (Historical information; not tested on animals for cosmetics)
ATE US (vapors)	124.700 mg/l/4h (Historical information; not tested on animals for cosmetics)
ATE US (dust, mist)	124.700 mg/l/4h (Historical information; not tested on animals for cosmetics)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
NOTE: Alcoholic beverages only; not applicable to this product. This product uses denatured alcohol.	

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : Not classified
Aspiration hazard : Not classified
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ethyl alcohol (64-17-5) (Historical information; not tested on animals for cosmetics)	
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and degradability

Not established.

12.3. Bioaccumulative potential

Ethyl alcohol (64-17-5)	
Log Pow	-0.32

LIVING PROOF FULL DRY VOLUME BLAST

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on global warming : No known ecological damage caused by this product.
Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.


SECTION 14: Transport information

Consult the associated transport regulations for available and applicable exceptions or exemptions.

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols, 2.1
UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols
Technical Shipping Name (DOT) : Not applicable
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Subsidiary hazard class (DOT) : None
Packing group (DOT) : None
Hazard labels (DOT) : LTD QTY - Limited quantity



DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Special Provisions (49 CFR 172.102) : N82
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A
DOT Vessel Stowage Other : 25, 87, 126
Response Guide (ERG) Number : 126
Other information : No supplementary information available.

Transportation of Dangerous Goods

In accordance with TDG


UN-No. (TDG) : UN1950
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas
Subsidiary hazard classes : None
Transport document description : UN1950 AEROSOLS, 2.1
Proper Shipping Name (Transportation of Dangerous Goods) : AEROSOLS

LIVING PROOF FULL DRY VOLUME BLAST

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Technical Shipping Name (TDG) : Not applicable
Hazard labels (TDG) : LTD QTY - Limited quantity




Packing group : None
TDG Special Provisions : 80,107
Explosive Limit and Limited Quantity Index : 1 L
Passenger Carrying Road Vehicle or Passenger : 75L
Carrying Railway Vehicle Index

Transport by sea

In accordance with IMDG

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1, LTD QTY
UN-No. (IMDG) : UN 1950
Proper Shipping Name (IMDG) : AEROSOLS
Technical Shipping Name (IMDG) : Not applicable
Transport hazard class(es) (IMDG) : 2.1
Subsidiary hazard class(es) (IMDG) : None
Danger labels (IMDG) : LTD QTY - Limited quantity



Packing group (IMDG) : Not applicable
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Limited Quantities (IMDG) : SP277
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

In accordance with IATA

May also be transported as a consumer commodity when classified as ID8000 under Class 9 Miscellaneous Dangerous Goods.

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1
UN-No. (IATA) : UN 1950
Proper Shipping Name (IATA) : Aerosols, flammable
Technical Shipping Name (IATA) : Not applicable
Transport hazard class(es) (IATA) : 2.1
Subsidiary hazard class(es) (IATA) : None

LIVING PROOF FULL DRY VOLUME BLAST

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Danger labels (IATA) : 2.1, LTD QTY - Limited quantity



Packing group (IATA)	: Not applicable
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product does not contain a toxic chemical in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

Canada-Regulations

No additional information available

EU-Regulations

No additional information available

National Regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

Ethyl alcohol (64-17-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity -	U.S. - California - Proposition 65 -	Non-significant risk level
Yes NOTE: Alcoholic beverages only; not applicable to this product. This product uses denatured alcohol.	Yes NOTE: Alcoholic beverages only; not applicable to this product. This product uses denatured alcohol.	No	No	
Hydrofluorocarbon 152a (200-866-1)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List				
Ethyl alcohol (64-17-5)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				
tert-Butyl alcohol (75-65-0)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List				
Butane (106-97-8)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List				

LIVING PROOF FULL DRY VOLUME BLAST

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Magnesium Carbonate (546-93-0)

U.S. - Massachusetts - Right To Know List

SECTION 16: Other information

Revision date : 04 June 2020

Data sources : DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H-phrases listed in Sections 2-15:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H350	May cause cancer

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product