

JOHN PAUL MITCHELL SYSTEMS					<h1 style="text-align: center;">SAFETY DATA SHEET</h1>								Page 1 of 6 PM-174	
Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards					SDS Revision: 1.0				SDS Revision Date: 11/10/2022					

1. PRODUCT & COMPANY IDENTIFICATION													
1.1	Product Name:	AWAPUHI WILD GINGER STYLING TREATMENT OIL											
1.2	Chemical Name:	NA											
1.3	Synonyms:	JPMS-113; Awapuhi Wild Ginger Styling Treatment Oil											
1.4	Trade Names:	Paul Mitchell® Awapuhi Wild Ginger Styling Treatment Oil											
1.5	Product Use:	Cosmetics											
1.6	Distributor's Name:	John Paul® Mitchell Systems											
1.7	Distributor's Address:	20705 Centre Pointe Parkway, Santa Clarita, CA 91350 USA											
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300											
1.9	Business Phone / Fax:	+1 (661) 298-0390 / +1 (661) 298-0390											

2. HAZARDS IDENTIFICATION													
2.1	Hazard Identification:	Prepared in accordance with UN Globally Harmonized standards. Intended to comply with OSHA 29 CFR 1910.1200. Canadian WHMIS and Australian Work Health and Safety WARNING! FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. Classification: Flam. Liq. 3, Eye Irrit. 2B											
2.2	Label Elements:	Hazard Statements (H): H226 – Flammable liquid and vapor. H320 – Causes eye irritation. Precautionary Statements: P210 – Keep away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. P233 – Keep container tightly closed. P243 – Take action to prevent static discharges. P264 – Wash thoroughly with soap and water after handling. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P337+P317 – If eye irritation persists: Get medical help. P370+P378 – In case of fire, CO ₂ , halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).											
2.3	Other Warnings:	KEEP OUT OF REACH OF CHILDREN.											

3. COMPOSITION & INGREDIENT INFORMATION														
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					ppm		ppm			ppm				
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
CYCLOPENTASILOXANE	541-02-6	GY59452000	208-764-9	78-83	NA	NA	NF	NF	NA	NA	NA	NA		
Flam Liq. 4; Eye Irrit. 2B; H227, H320														
PROPRIETARY BLEND	NA	NA	NA	17-22	NA	NA	NF	NF	NA	NA	NA	NA		

4. FIRST AID MEASURES	
4.1	First Aid:
	<p>Ingestion: If ingested, do not induce vomiting. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>Eyes: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally.</p> <p>Skin: Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes.</p> <p>Inhalation: Remove victim to fresh air at once. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Keep person warm, quiet and get medical attention.</p>
4.2	Effects of Exposure:
	<p>Ingestion: If product is swallowed, may cause gastrointestinal disturbance.</p> <p>Eyes: Exposure to fumes/vapors may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation and watering.</p> <p>Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p>Inhalation: May cause mild, transient respiratory irritation. Avoid prolonged contact with concentrated vapors or mists.</p>
4.3	Symptoms of Overexposure:
	<p>Ingestion: Nausea, intestinal discomfort, vomiting and/or diarrhea.</p> <p>Eyes: Exposure to fumes/vapors may cause eye irritation. Symptoms of overexposure may include redness, itching, irritation, and watering.</p> <p>Skin: May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals.</p> <p>Inhalation: Coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose, and respiratory tract. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches, and nausea.</p>

JOHN PAUL MITCHELL SYSTEMS		<h1>SAFETY DATA SHEET</h1>					Page 2 of 6 PM-174																
Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards					SDS Revision: 1.0		SDS Revision Date: 11/10/2022																
<h2>4. FIRST AID MEASURES- cont'd</h2>																							
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of fumes/vapors can cause coughing, wheezing, shortness of breath, impaired pulmonary function. Irritation or soreness in throat, nose and respiratory tract.																					
4.5	Chronic Health Effects:	Possible allergic dermatitis in some sensitive individuals.																					
4.6	Target Organs:	Eyes, Skin																					
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions, and disorders of the target organs (eyes, skin) or impaired kidney function may be more susceptible to the effects of this substance.					<table border="1"> <tr> <td colspan="2">HEALTH</td> <td>1</td> </tr> <tr> <td colspan="2">FLAMMABILITY</td> <td>2</td> </tr> <tr> <td colspan="2">PHYSICAL HAZARDS</td> <td>0</td> </tr> <tr> <td colspan="2">PROTECTIVE EQUIPMENT</td> <td>B</td> </tr> <tr> <td>EYES</td> <td>SKIN</td> <td></td> </tr> </table>		HEALTH		1	FLAMMABILITY		2	PHYSICAL HAZARDS		0	PROTECTIVE EQUIPMENT		B	EYES	SKIN	
HEALTH		1																					
FLAMMABILITY		2																					
PHYSICAL HAZARDS		0																					
PROTECTIVE EQUIPMENT		B																					
EYES	SKIN																						
<h2>5. FIREFIGHTING MEASURES</h2>																							
5.1	Fire & Explosion Hazards:	WARNING! FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, sparks & open flame. Keep container closed. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container																					
5.2	Extinguishing Methods:	Water, Foam, CO ₂ , Dry Chemical, Halon (if authorized)																					
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand) and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personnel. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.																					
<h2>6. ACCIDENTAL RELEASE MEASURES</h2>																							
6.1	Spills	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE).</p> <p>For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.</p>																					
<h2>7. HANDLING & STORAGE INFORMATION</h2>																							
7.1	Work & Hygiene Practices:	Do not eat, drink, or smoke while handling this product.																					
7.2	Storage & Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat and open flames. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage.																					
7.3	Special Precautions:	Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.																					
<h2>8. EXPOSURE CONTROLS & PERSONAL PROTECTION</h2>																							
8.1	Exposure Limits: ppm (mg/m ³)	ACGIH		NOHSC			OSHA		OTHER														
		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH														
CHEMICAL NAME(S)		NA	NA	NF	NF	NF	NA	NA	NA														
8.2	Ventilation & Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).																					
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, EU member states, or Australia.																					
8.4	Eye Protection:	AVOID EYE CONTACT DUE TO SENSITIZATION POTENTIAL. None required under normal conditions of use. Safety glasses with side shields should be used when handling large quantities (e.g., ≥ 1 gallon) of this product.																					

JOHN PAUL MITCHELL SYSTEMS		<h1>SAFETY DATA SHEET</h1>		Page 3 of 6 PM-174	
Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards			SDS Revision: 1.0		SDS Revision Date: 11/10/2022












8. EXPOSURE CONTROLS & PERSONAL PROTECTION – cont'd					
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon), wear rubber or impervious plastic gloves.			
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available.			


9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Appearance:	Slightly hazy semi viscous liquid			
9.2	Odor:	Ginger			
9.3	Odor Threshold:	NA			
9.4	pH:	NA			
9.5	Melting Point/Freezing Point:	NA			
9.6	Initial Boiling Point/Boiling Range:	NA			
9.7	Flashpoint:	< 47.8 °C (< 118 °F) TCC			
9.8	Upper/Lower Flammability Limits:	LEL: NA; UEL: NA			
9.9	Vapor Pressure:	NA			
9.10	Vapor Density:	NA			
9.11	Relative Density:	0.92-0.97			
9.12	Solubility:	NA			
9.13	Partition Coefficient (log P _{ow}):	NA			
9.14	Autoignition Temperature:	NA			
9.15	Decomposition Temperature:	NA			
9.16	Viscosity:	500-800 cPs (RVD#4@100rpm, 60sec)			
9.17	Other Information:	NA			

10. STABILITY & REACTIVITY					
10.1	Stability:	This product is stable.			
10.2	Hazardous Decomposition Products:	If exposed to <u>extremely high temperatures</u> , products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen).			
10.3	Hazardous Polymerization:	Will not occur.			
10.4	Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.			
10.5	Incompatible Substances:	Strong oxidizers, peroxides or strong acids.			

11. TOXICOLOGICAL INFORMATION					
11.1	Routes of Entry:	Inhalation:	NO	Absorption:	YES
					Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components, but is not presented in this document.			
11.3	Acute Toxicity:	See Section 4.4			
11.4	Chronic Toxicity:	See Section 4.5			
11.5	Suspected Carcinogen:	This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to www.P65Warnings.ca.gov			
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.			
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.			
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.			
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.			
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.			
11.7	Irritancy of Product:	See Section 4.3			
11.8	Biological Exposure Indices:	NE			
11.9	Physician Recommendations:	Treat symptomatically.			

12. ECOLOGICAL INFORMATION					
12.1	Environmental Stability:	There are no specific data available for this product.			
12.2	Effects on Plants & Animals:	There are no specific data available for this product.			
12.3	Effects on Aquatic Life:	There are no specific data available for this product.			

JOHN PAUL MITCHELL SYSTEMS		SAFETY DATA SHEET		Page 4 of 6 PM-174
Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards			SDS Revision: 1.0	SDS Revision Date: 11/10/2022
13. DISPOSAL CONSIDERATIONS				
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations.		
13.2	Special Considerations:	Contact the federal, state or provincial environmental authority to determine suitability for recycling and or proper disposal requirements. U.S. EPA Hazardous Waste (Characteristic – Ignitable): D001		
14. TRANSPORTATION INFORMATION				
The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.				
14.1	49 CFR (GND):	UN1993, FLAMMABLE LIQUID, N.O.S. (cyclopentasiloxane), 3, III, (LTD QTY, IP VOL ≤ 5.0 L)		
14.2	IATA (AIR):	UN1993, FLAMMABLE LIQUID, N.O.S. (cyclopentasiloxane), 3, III, (LTD QTY, IP VOL ≤ 1.0 L) or ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L)	 or 	
14.3	IMDG (OCN):	UN1993, FLAMMABLE LIQUID, N.O.S. (cyclopentasiloxane), 3, III, (LTD QTY, IP VOL ≤ 5.0 L)		
14.4	TDGR (Canadian GND):	UN1993, FLAMMABLE LIQUID, N.O.S. (cyclopentasiloxane), 3, III, (LTD QTY, IP VOL ≤ 5.0 L)		
14.5	ADR/RID (EU):	UN1993, FLAMMABLE LIQUID, N.O.S. (cyclopentasiloxane), 3, III, (LTD QTY, IP VOL ≤ 5.0 L)		
14.6	SCT (MEXICO):	UN1993, FLAMMABLE LIQUID, N.O.S. (cyclopentasiloxane), 3, III, (LTD QTY, IP VOL ≤ 5.0 L)		
14.7	ADGR (AUS):	UN1993, FLAMMABLE LIQUID, N.O.S. (cyclopentasiloxane), 3, III, (LTD QTY, IP VOL ≤ 5.0 L)		
14.8	OTHER:	This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)		
15. REGULATORY INFORMATION				
15.1	SARA Reporting Requirements:	This product does not contain any substances subject to SARA Title III, Section 313 reporting requirements.		
15.2	SARA TPQ:	There are no specific Threshold Planning Quantities for the components of this product.		
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.		
15.4	CERCLA Reportable Quantity:	NA		
15.5	Other Federal Requirements:	This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA.		
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects)	 	
15.7	State Regulatory Information:	No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information, go to www.P65warnings.ca.gov		
15.8	Other Requirements:	NA		

JOHN PAUL MITCHELL SYSTEMS		<h1 style="text-align: center;">SAFETY DATA SHEET</h1>		Page 5 of 6 PM-174
Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards			SDS Revision: 1.0	SDS Revision Date: 11/10/2022
<h2 style="text-align: center;">16. OTHER INFORMATION</h2>				
16.1	Other Information:	WARNING! FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. Use as directed. Discontinue use immediately if irritation develops. Keep away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Keep container tightly closed. Take action to prevent static discharges. Wash thoroughly with soap and water after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire, CO ₂ , halon (if permitted), dry chemical, or foam for extinction. Store in a well-ventilated place. Keep cool. KEEP OUT OF REACH OF CHILDREN.		
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.		
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & John Paul® Mitchell Systems', knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.		
16.4	Prepared for:	John Paul® Mitchell Systems 20705 Centre Pointe Parkway, Santa Clarita, CA 91350 USA Tel: +1 (661) 298-0400 Fax: +1 (661) 298-0390	<div style="border: 1px solid black; padding: 5px; text-align: center;"> JOHN PAUL MITCHELL SYSTEMS </div>	
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com		

JOHN PAUL MITCHELL SYSTEMS	<h1 style="margin: 0;">SAFETY DATA SHEET</h1>	Page 6 of 6 PM-174
Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards		SDS Revision: 1.0
DEFINITION OF TERMS		

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A	
B	
C	
D	
E	
F	

G	
H	
I	
J	
K	
X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Protective Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive

FLAMMABILITY

1

2

HEALTH

W

SPECIAL PRECAUTIONS

REACTIVITY

TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD ₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD ₁₀ , LD ₁₀ , & LD ₀ or TC, TC ₀ , LC ₁₀ , & LC ₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{OW} or log K _{OC}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment